

BOSS 762 Series Indoor / Semi Outdoor LED Display Specifications

- Application:**
- Airport, railway, station, port, traveler guidance.
 - Call center, factory, bank, foreign exchange, hospital.
 - Welcome message, advertisement, etc.



Departure Hall, Lv5, Kuala Lumpur International Airport (KLIA)

| Rows | Columns | Approx. Display Dimension HxW | Char Height Per Line | 8.6" Char's Per Line | Max Power Consumption | Approx. Weight |
|------|---------|-------------------------------|----------------------|----------------------|-----------------------|----------------|
| 32 | 128 | 9.6" x 38.4" | 9.6" / 1 | 21 / 2 | 100W | 4kg |
| 32 | 192 | 9.6" x 57.6" | 4.5" / 2 | 32 / 2 | 150W | 6kg |
| 32 | 256 | 9.6" x 76.8" | 3" / 3 | 42 / 2 | 200W | 8kg |
| 32 | 320 | 9.6" x 96" | 2.1" / 4 | 53 / 2 | 250W | 10kg |

Can be customize according to requirements

| | |
|------------------------|---|
| Pixel (LED) Color: | Each dot can be red, green, or amber; |
| Pixel Pitch: | 0.3" (7.62mm) |
| Character Set: | International Character Set |
| Memory Retention: | Typically one month |
| Message Presentation: | - Consisting of various modes: Hold, Rotate, Roll Up, Roll Down. - User programmable logos or graphics |
| Clock / Date: | Date in multiple formats and time in 12/24-hour formats |
| Serial Communication: | RS232, RS485, Dial-up Modem |
| Power: | 240 VAC ±10% 60Hz |
| Operating Temperature: | -10°C~+60 °C |
| Energy Efficient: | Consume up to less than 1/40 the power of incandescent |